



ROUND STEEL TANKS F & H SERIES





Recommended tightening
torque for 3/8" BSP: 10 Nm



Description	Spare part code	Assembly code	L (mm)	Weight	Actual filling volume (lt)
					Vertical
0,7 l cylindrical vertical mounting	E50403001	0,7FV	120	0,56 Kg	0,52
1,2 l cylindrical vertical mounting	E50403002	1,2FV	186	0,77 Kg	0,9



Recommended tightening
torque for 3/8" BSP: 10 Nm



Description	Spare part code	Assembly code	L (mm)	ØD (mm)	Weight	Actual filling volume (lt)	
						Horizon.	Vert.
1,7 l cylindrical horizontal / vertical mounting	E50404004	1,7H / 1,7HV	170	120	0,64 Kg	1,5	1,2
2,4 l cylindrical horizontal / vertical mounting	E50404006	2,4H / 2,4HV	170	150	0,8 Kg	2,4	1,8

Material	Fe P04-EN10130 steel sheet 1,5 mm thickness
Fluid	Mineral based oil ISO/DIN 6743/4
Working temperature	-15 / +70°C

Note: the piping kit, standard suction filter, filler/breather and discharge plug are included when specifying the tank in PPM assembly code

When ordering spare parts, only the discharge plug and filler/breather are included