



P	Numero documento	Description_EN	Q
1	UA	universal A type PPC body with 3 lateral cavities	1
2	1,6 12DC_T	12VDC motor 1600W Φ 114 + thermal switch	1
3	S150T 12DC 112 C	starting relay 12VDC 150A for Φ 114 motors + cable mounting kit	1
4	G1,6	gear pump group 1 - 1,6cc/rev G series	1
5	E36200001	coupling PPC Φ 114/125 DC motors with pumps group 1	1
6	J	check valve ball type 3/4-16UNF	1
7	V250	relief valve 3/4-16UNF 250 bar max	1
8	A	NC solenoid 2/2 way 3/4-16UNF poppet valve	1
9	12DC_M630	coil 12VDC ED100% + electric connector DIN 43650-A	1
10	3(04)	fixed pressure compensated flow control valve 3l/min, Φ 12,7mm with o-ring	1
11	TADPH00003	plastic elbow flow discharge 1/4 BSPP 207mm	1
12	P_Tport	1/4 BSP plug with copper washer on T port	1
13	PP02E40	elbow suction pipe 3/8 BSP 40mm	1
14	E34100005	standard suction strainer	1
15	3L	3L square plastic tank horizontal + filler & breather plug	1

03			
02			
01			
IR	MODIFICATION DESCRIPTION		SIGN DATE
Hydronit s.r.l. via Pastrengo 62 Varedo (MB) Italy		SIGNATURE	DATE
		Drawn by S. Vanzati 04/06/2019 Checked by M. Saini 04/06/2019	Description
Scale 1:4 Code PPC161116HY-ECOMMERCE-115255		IR	01
		This document is confidential and can not be copied nor disclosed to a third party without written consent. In presence of outdated norms, please refer to the updated ones.	