



Posizione	Numero documento	Description_EN	Quantità
1	U4	universal 4 type PPC body for 4 way cartridge valves	1
2	2,2 24DC_T	24VDC motor 2200W ϕ 114 + thermal switch	1
3	S150T 24DC 112	starting relay 24VDC 150A + mounting kit for ϕ 114 motors with copper plate	1
4	E36200001	coupling PPC ϕ 114/125 DC motors with pumps group 1	1
5	L	plug 3/4-16UNF basic	2
6	V250	relief valve 3/4-16UNF 250 bar max	1
7	4VA2	4/3 way solenoid valve, center P to T	1
8	24DC_M630	coil 24VDC ED100% + electric connector DIN 43650-A	2
9	PP01370	suction/return line pipe 1/4 BSP 370mm	1
10	K2,7	gear pump group 1 - 2,8cc/rev K series	1
11	PP02125	suction pipe 3/8 BSP 125mm	1
12	SFEP01D	relief valve standard return dumpener	1
13	E34100005	standard suction strainer	1
14	5MV	5L square plastic tank vertical + filler & breather plug	1

03			
02			
01	PP01370 instead of RETURN-KIT		KM06/10/22
IR	MODIFICATION DESCRIPTION		SIGN. DATE
 via Pastrengo 62 Varedo (MB) Italy		SIGNATURE	DATE
		Drawn by <u>S. Vanzati</u> 06/10/2022 Checked by <u>A. Gambusera</u> 06/10/2022	Description
Scale 1:4		Code	IR
General tolerance: EN-22768 ISO-2768 : V-V		PPC180601HY-ECOMMERCE-093938 01	
This document is confidential and can not be copied nor disclosed to a third party without written consent. In presence of outdated norms, please refer to the updated ones.			