



Posizione	Numero documento	Description_EN	Quantità
1	UA	universal A type PPC body with 3 lateral cavities	1
2	E0,55AC S4 71	integral motor 0,55kW S3 1-ph 4-pole 230V 50Hz frame 71 for PPC	1
3	K0,9	gear pump group 1 - 0,89cc/rev K series	1
4	E36100000	coupling PPC AC motors all sizes with pumps group 1	1
5	J	check valve ball type 3/4-16UNF	1
6	V350	relief valve 3/4-16UNF 350 bar max	1
7	B	NC solenoid 2/2 way 3/4-16UNF poppet valve with emergency	1
8	24AC_M631	coil 24VAC ED100% with integral rectifier + electric connector DIN 43650-A	1
9	2(04)	fixed pressure compensated flow control valve 2l/min, $\Phi$ 12,7mm with o-ring	1
10	PP01370	suction/return line pipe 1/4 BSP 370mm	1
11	PP02142	suction pipe 3/8 BSP 142mm	1
12	E34100005	standard suction strainer	1
13	5M-S02	5 l horizontal plastic square tank + filling cap on the bottom side	1
14	P_Tport	1/4 BSP plug with copper washer on T port	1
15	SFEP01D	relief valve standard return dumpener	1

03			
02			
01	PP01370 instead of RETURN-KIT		KM/13/10/22
IR	MODIFICATION DESCRIPTION		SIGN. DATE
 via Pastrengo 62 Varedo (MB) Italy		SIGNATURE	DATE
		Drawn by S. Vanzati	24/05/2019
		Checked by A. Gambusera	24/05/2019
		Scale	Code
		1:5	PPC190228HY-ECOMMERCE-141014
		IR	01
General tolerance: EN-22768 ISO-2768: V-V		This document is confidential and can not be copied nor disclosed to a third party without written consent in presence of outdated norms, please refer to the updated ones.	